



MATERIAL (SAFETY DATA SHEET)

PRODUCT PROBOND 5060
according to Regulation (EC) No 1907/2006

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier: 30021, 30028, 30029, 30520, 30720

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixer: Adhesives, sealants
Uses advised against: any non-intended use.

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier
Delta Kits Inc.
1090 Bailey Hill Rd. Suite A
Eugene Or. 97402
Tel: 800-548-8332
Fax: (541)345-1591

1.4. Emergency telephone number:

Chemtel
(800)-255-3925 US
(813)-248-0585 Int.

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC
Indications of danger: Xi - Irritant, N - Dangerous for the environment
R phrases:
Irritating to eyes, respiratory system and skin.
May cause sensitization by skin contact.
Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification according to Regulation (EC No. 1272/2008)[CLP]
Hazard categories:
Skin corrosion/irritation: Skin Irrit. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Respiratory/skin sensitization: Skin Sens. 1
Specific target organ toxicity - single exposure: STOT SE 3
Hazardous to the aquatic environment: Aquatic Acute 1
Hazard Statements:
Causes skin irritation.
May cause respiratory irritation.
Very toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazardous components which must be listed on the label
2-hydroxyethyl methacrylate
exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

Signal word: Warning
Pictograms: GHS07-GHS09

Hazard statements
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P312 Call POISON CENTER/doctor if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container to in accordance with official regulations.

Special labelling of certain mixtures
EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazard components

| EC NO | Chemical name | Quantity |
|--------------|--|-----------|
| CAS No | Classification according to Directive 67/548/EEC | |
| Index No | Classification according to Regulation (EC) No. 1272/2008 [CLP] | |
| REACH NO | | |
| 212-782-2 | 2-hydroxyethyl methacrylate | 45 - <50% |
| 868-77-9 | Xi - Irritant R36/38-43 | |
| 607-124-00-X | Eye Irrit. 2, Skin Irrit. 2, Skin Sens.1: H319 H315 H317 | |
| 227-561-6 | exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate | 45 - <50% |
| 5888-33-5 | Xi - Irritant, N - Dangerous for the environment R36/37/38-43-50-53 | |
| | Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1B, STOT SE 3, Aquatic Acute 1 (M-Factor = 1), Aquatic Chronic 1 (M-Factor = 1); H315 H319 H317 H335 H400 H410 | |
| 219-784-2 | [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | 1 - <5% |
| 2530-83-8 | Xi - Irritant R41 | |
| | Eye Dam. 1; H318 | |

Full text of R-, H- and EUH-phrases: see section 16.

Further Information

Product does not contain listed SVHC substances.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or if you feel unwell, seek medical advice immediately (show safety data sheet if possible).



After inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of irritation of the respiratory tract seek medical advice.

In the case of lung irritation: Primary treatment using corticoid spray, e.g. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks).

After contact with skin

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do not induce vomiting. Rinse mouth thoroughly with water. Let water be swallowed in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. Call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Dry extinguishing powder. Foam. Water spray. Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical resistant suit. In case of fire and/or explosion do not breathe fumes.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray/stream to protect personnel and to cool endangered containers.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.

Do not breathe gas/vapour/spray. Avoid contact with skin, eye and clothing.

Wear personal protection equipment. (refer to chapter 8)

6.2. Environmental precautions

Do not empty into drains or the aquatic environment. Prevent spreading over great surfaces (e.g. by damming or installing oil booms). In case of leakage into waters, ground or the drainage system, the appropriate authorities must be informed.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Ventilate affected area.

Treat the assimilated material according to the section on waste disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Advice on safe handling

Provide adequate ventilation.

Wear suitable protective clothing. (Refer to chapter 8.)

Advice on protection against fire and explosion

Usual measures for fire prevention.

Further information on handling

Do not breathe gas/vapor/spray. Avoid contact with skin, eye and clothing.

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep container dry.

Advice on storage compatibility

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances.

Infectious substances.

Further information on storage conditions

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Additional advice on limit values

To date, no national limit values exist.

8.2. Exposure controls

Appropriate engineering controls

In case of open handling, use devices with built-in suction where possible. If suction of the immediate vicinity is impossible or insufficient, adequate airing of the working place must be ensured.

Protective and hygiene measures

Always close containers tightly after the removal of product. Do not eat, drink, smoke or sneeze at the workplace. Wash hands before breaks and at the end of work. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Used working clothes should not be used outside the work area. Street clothing should be stored separately from work clothing. Protect skin by using skin protective cream.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

Hand protection

Pull-over gloves of rubber. DIN EN 374

Suitable material:

(Breakthrough time \geq 480 min, penetration time (maximum wearing period): 160 min)

CR (polychloroprene's, Chloroprene rubber). (0,5 mm)

FKM (fluororubber). (0,4 mm)

Butyl rubber. (0,5 mm)

Before using check leak tightness / impermeability. In case of reutilization, clean gloves before taking off and store in well-aired place.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Skin protection

Protective clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection required in case of:

insufficient ventilation.

Generation/formation of aerosols

Generation/formation of mist

Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Type : A / P2/P3

The filter class must be suitable for the maximum contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, closed-circuit breathing apparatus must be used!

Environmental exposure controls

Do not empty into drains or the aquatic environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | | |
|-----------------|----------------|-------------|
| Physical state: | Liquid | |
| Colour: | Clear | |
| Odour: | characteristic | Test method |
| pH-Value: | Not Determined | |

Changes in the physical state

| | |
|--|----------------|
| Melting point: | Not Determined |
| Initial boiling point and boiling range: | Not Determined |
| Flash point: | Not Determined |

Explosive properties

none/none

| | |
|-------------------------|----------------|
| Lower explosion limits: | Not Determined |
| Upper explosion limits: | Not Determined |

Oxidizing properties

none/none

| | |
|----------------------|----------------|
| Vapour pressure: | Not Determined |
| Density: | Not Determined |
| Viscosity / dynamic: | Not Determined |

9.2. Other information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Hazardous polymerization: Protect from direct sunlight. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

10.2. Chemical stability

Stable under normal storage and handling conditions.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: Light. UV-radiation/sunlight. heat. cooling. moisture.

10.5. Incompatible materials

Materials to avoid: Strong acid. Oxidizing agents, strong. Alkalis (alkalis), concentrated.

10.6. Hazardous decomposition products

Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂).

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Toxicokinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

| CAS No | Chemical name | Exposer routes | Method | Dose | Species | Source |
|-----------|---|-------------------------|--------|-------------|--------------------|--------------|
| 868-77-9 | 2-hydroxyethyl methacrylate | oral | LD50 | >5000mg/kg | Rat. | ECHA Dossier |
| | | dermal | LD50 | >5000mg/kg | Rabbit. | ECHA Dossier |
| 5888-33-5 | exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate | Oral | LD50 | 4350 mg/kg | Rat. | ECHA Dossier |
| | | dermal | LD50 | >2000 mg/kg | Rabbit | ECHA Dossier |
| 2530-83-8 | [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | oral | LD50 | >5000mg/kg | Rat. (OECD 401) | ECHA Dossier |
| | | dermal | LD50 | >2000 mg/kg | Rabbit. (OECD 402) | ECHA Dossier |
| | | inhalative (4h) aerosol | LC50 | >5,3 mg/l | Rat. (OECD 403) | ECHA Dossier |

Irritation and corrosivity

Causes skin irritation.
Causes serious eye irritation.

Sensitizing effects

May cause an allergic skin reaction. (2-hydroxyethyl methacrylate), (exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)
Product is: sensitizing.
People who suffer from skins problems, asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

STOT-single exposure

May cause respiratory irritation. (exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.
2-hydroxyethyl methacrylate (CAS-No.: 868-77-9):
Sub chronic oral toxicity: NOAEL = 30 mg/kg (90d, Rat.)
literature information: ECHA Dossier

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

2-hydroxyethyl methacrylate (CAS-No.: 868-77-9):
No experimental indications of mutagenicity in-vitro exist.
Reproductive toxicity: NOAEL = 1000 mg/kg (Rat.)
Developmental toxicity/teratogenicity: NOAEL = 50 mg/kg (Rabbit.)
literature information: ECHA Dossier

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate (CAS-No.: 5888-33-5):
No experimental indications of mutagenicity in-vitro exist.
Reproductive toxicity: NOAEL = 100 mg/kg(bw)/day (OECD 422; Rat.)
Developmental toxicity/teratogenicity: NOAEL = 500 mg/kg(bw)/day (OECD 421; Rat.)
literature information: ECHA Dossier

[3-(2,3-Epoxypropoxy)propyl]trimethoxysilane (CAS-No.: 2530-83-8):
In-vitro mutagenicity: OECD Guideline 471 (Bacterial Reverse Mutation Assay) = positive.
Carcinogenicity: (Rat.) NOAEL = >5 mg/kg
Developmental toxicity/teratogenicity: (Rat.) NOAEL = >500 mg/kg
Reproductive toxicity: (Rabbit.) NOAEL = >200 mg/kg
literature information: ECHA Dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

| CAS No | Chemical name | | | [H] [d] | Species | Source |
|-----------|---|--------|------------|---------|---|--------------|
| | Aquatic Toxicity | Method | Dose | | | |
| 868-77-9 | 2-hydroxyethyl methacrylate | | | | | |
| | Acute fish toxicity | LC50 | 227 mg/l | 96h | Pimephales promelas | ECHA Dossier |
| | Acute algae toxicity | ERC50 | 836 mg/l | 72h | Selenastrum capricornutum | ECHA Dossier |
| | Acute crustacea toxicity | EC50 | 380 mg/l | 48h | Daphnia magna | ECHA Dossier |
| 5888-33-5 | exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate | | | | | |
| | Acute fish toxicity | LC50 | 0,704 mg/l | 96h | Danio rerio (OECD 203) | ECHA Dossier |
| | Acute algae toxicity | ERC50 | 0,596 mg/l | 72h | Pseudokirchnerella subcapitata (OECD 201) | ECHA Dossier |
| | Crustacea toxicity | NOEC | 0,092 mg/l | 21d | Daphnia magna (OECD 211) | ECHA Dossier |
| 2530-83-8 | [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | | | | | |
| | Acute fish toxicity | LC50 | (55) mg/l | 96h | Cyprinus carpio | ECHA Dossier |
| | Acute crustacea toxicity | EC50 | 324 mg/l | 48h | Simocephalus vetulus | ECHA Dossier |
| | Crustacea toxicity | NOEC | >100 mg/l | 21d | Daphnia magna | ECHA Dossier |

12.2. Persistence and degradability

| CAS No | Chemical name | | | Value | d | Source |
|-----------|---|--|------|-------|----|--------------|
| | Method | | | | | |
| | Evaluation | | | | | |
| 868-77-9 | 2-hydroxyethyl methacrylate | | | | | |
| | OECD 301C / ISO 9408 / EWG 92/69 Anhang V, C.4-F | | .92% | | 14 | ECHA Dossier |
| | Easily biodegradable (concerning to the criteria of the OECD) | | | | | |
| 5888-33-5 | exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate | | | | | |
| | OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D | | 51% | | 28 | ECHA Dossier |
| | Product is not easily biodegradable. | | | | | |
| 2530-83-8 | [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | | | | | |
| | OECD 301A / ISO 7827 / EEC 92/69 annex V, C.4-A | | 37% | | 28 | ECHA Dossier |
| | Not easily bio-degradable (according to OECD-criteria). | | | | | |

12.3. Bioaccumulative potential

| CAS No | Chemical name | Log Pow |
|-----------|---|---------|
| 868-77-9 | 2-hydroxyethyl methacrylate | 0,47 |
| 5888-33-5 | exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate | 4,52 |
| 2530-83-8 | [3-(2,3-Epoxypropoxy)propyl]trimethoxysilane | -2,6 |

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not empty into drains or the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Waste disposal according to official state regulations. Consult the local waste disposal expert about waste disposal. Cleaned containers may be recycled.

Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

80409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Waste disposal number of used product

80409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other dangerous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by dangerous substances
Classified as hazardous waste.

Contaminated packaging

Handle contaminated packaging in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III



Hazard label:

9

Classification code:

M6

Special Provisions:

274 335 601

Limited quantity

5L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

E

Inland waterways transport (ADN)

14.1. UN number:

UN3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III



Hazard label:

9

Classification code:

M6

Special Provisions:

274 335 601

Limited quantity

5L

Excepted quantity:

E1

Transport category:

3

Hazard No:

90

Tunnel restriction code:

E

Marine transport (IMDG)

14.1. UN number:

UN3082

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III



Hazard label:

9

Marine pollutant:

YES

Special Provisions:

274, 335

Limited quantity

5L

Excepted quantity:

E1

EmS:

F-A, S-F

Hazard No:

90

Air transport (ICAO)

14.1. UN number:

UN3082

14.2. UN proper shipping name:


ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III



Hazard label:

9

Special Provisions:

A97 A158

Limited quantity Passenger:

30 kg G

Passenger LQ:

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger:

964

IATA-max. quantity - Passenger:

450L

IATA-packing instructions - Cargo:

964

IATA-max. quantity - Cargo:

450L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
irrelevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): No information available.

2004/42/EC (VOC): No information available.

Additional information

The preparation is dangerous in the sense of Directive 1999/45/EC.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

Regulation 96/82/EC for danger control following severe accidents with dangerous substances: Appendix I, Part 2, No 9i, (Seveso II).

REACH 1907/2006 Appendix XVII, No 3

National regulatory information

Employment restrictions: Observe employment restrictions

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1,00; 19.03.2019, Initial release

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OSHA: Concerning the International Transport of Dangerous Goods by Rail)

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern

TRGS Technische Regeln für Gefahrstoffe

TSCA: Toxic Substances Control Act

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe

WGK: Wassergefährdungsklasse

Relevant R-phrases (Number and full text)

36/37/38 Irritating to eyes, respiratory system and skin.

36/38 Irritating to eyes and skin.

41 Risk of serious damage to eyes.

43 May cause sensitization by skin contact.

50 Very toxic to aquatic organisms.

53 May cause long-term adverse effects in the aquatic environment.

Relevant H- and EUH-phrases (Number and full text)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Issue Date: 2015-02-13

Revision Date: 2021-07-13

To the best of our knowledge, the information contained herein is accurate. However, Delta Kits Inc. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.